


Product overview

Plastic Modular Belt Series



Straight Running Belt Overview

| | | | |
|---|---|---|--|
| <p>Pitch 8.00 mm (0.32 in)</p> | <p>Pitch 12.7 mm (0.50 in)</p> | <p>Pitch 12.7 mm (0.50 in)</p> | <p>Pitch 12.7 mm (0.50 in)</p> |
| <p>uni NTB Strength Index (POM)</p> <p>2000 N/m (137 lbf/ft)</p> | <p>uni M-PNB M1 Strength Index (POM)</p> <p>2000 N/m (137 lbf/ft)</p> | <p>uni M-QNB Strength Index (POM)</p> <p>19000 N/m (1302 lbf/ft)</p> | <p>uni M-SNB M3 Strength Index (POM)</p> <p>15000 N/m (1028 lbf/ft)</p> |
| <p>Pitch 12.7 mm (0.50 in)</p> | <p>Pitch 19.1 mm (0.75 in)</p> | <p>Pitch 25.4 mm (1.00 in)</p> | <p>Pitch 25.4 mm (1.00 in)</p> |
| <p>uni M-TTB Strength Index (POM)</p> <p>22500 N/m (1541 lbf/ft)</p> | <p>uni Light Strength Index (POM)</p> <p>10250 N/m (702 lbf/ft)</p> | <p>uni CNB Strength Index (POM)</p> <p>15700 N/m (1076 lbf/ft)</p> | <p>uni JCB Y Strength Index (POM)</p> <p>35000 N/m (2400 lbf/ft)</p> |
| <p>Pitch 25.4 mm (1.00 in)</p> | <p>Pitch 25.4 mm (1.00 in)</p> | <p>Pitch 25.4 mm (1.00 in)</p> | <p>Pitch 25.4 mm (1.00 in)</p> |
| <p>uni LPB Strength Index (POM)</p> <p>35000 N/m (2400 lbf/ft)</p> | <p>uni QNB Strength Index (POM)</p> <p>35000 N/m (2400 lbf/ft)</p> | <p>uni S-MPB Strength Index (POM)</p> <p>23500 N/m (1610 lbf/ft)</p> | <p>uni SNB M2 Strength Index (POM)</p> <p>23500 N/m (1610 lbf/ft)</p> |
| <p>Pitch 27.9 mm (1.10 in)</p> | <p>Pitch 38.1 mm (1.50 in)</p> | <p>Pitch 38.1 mm (1.50 in)</p> | <p>Pitch 50.0 mm (1.97 in)</p> |
| <p>uni OWL Strength Index (POM)</p> <p>12000 N/m (822 lbf/ft)</p> | <p>uni Light EP Strength Index (POM)</p> <p>10250 N/m (703 lbf/ft)</p> | <p>uni SSB Strength Index (POM)</p> <p>36000 N/m (2467 lbf/ft)</p> | <p>uni L-SNB Strength Index (POM)</p> <p>55000 N/m (3770 lbf/ft)</p> |



Straight Running Belt Overview




uni OPB
Strength Index (POM)





uni BLB
Strength Index (POM)



uni CPB
Strength Index (POM)




uni CSB
Strength Index (POM)





uni ECB
Strength Index (POM)




uni MPB
Strength Index (POM)




uni RTB M1
Strength Index (POM)




uni ULB
Strength Index (POM)



uni X-MPB
Strength Index (POM)




uni XLB
Strength Index (POM)





For further information,
please find the latest
version of our modular
datasheets at:
www.unichains.com



Side Flexing Belt Overview





uni Flex ASB
Strength Index (POM)





uni Flex OSB
Strength Index (POM)




uni Flex SNB
Strength Index (POM)




uni Flex ONE
Strength Index (POM)



uni Flex L-ASB
Strength Index (POM)



uni Flex L-OSB
Strength Index (POM)



Expert advice, quality solutions and local service for all your belting needs
www.ammeraalbeltech.com

Global Headquarters:
Ammeraal Beltech Holding B.V.
P.O. Box 38, 1700 AA Heerhugowaard
The Netherlands

T +31 72 575 1212
F +31 72 571 6455
info@ammeraalbeltech.com

This information is subject to alteration due to continuous development. Ammeraal Beltech will not be held liable for the incorrect use of the above stated information. This information replaces previous information. All activities performed and services rendered by Ammeraal Beltech are subject to general terms and conditions of sale and delivery, as applied by its operating companies.